

## Description

# Quick Turn–Lock Waveguide Transition Assembly

### BACKGROUND OF INVENTION

[0001] Field of the Invention

[0002] This invention relates to the precision and variable angle attachment between two waveguide components, for example the transition between a feed waveguide or transmitter output and a dual reflector antenna feed assembly. More particularly, the invention relates to a cost effective feed transition assembly with quick tool–less initial mounting and widely variable connection angle alignment features.

[0003] Description of Related Art

[0004] Microwave antennas commonly have a feed assembly linked to a transmitter or receiver by a waveguide. To minimize signal degradation, the waveguide components are precision formed to create closely aligned and gap

free interconnections. An aperture in the waveguide signal path may be aligned to select between vertical and horizontal polarization by alternating the aperture orientation by 90 degrees. In addition to primary orientation for a desired polarization, a fine tuning ability is desirable to enable optimizing the selected polarization.

[0005] Prior dual reflector microwave antennas have used an aperture slip ring with a plurality of bolt holes, each bolt hole in the form of an arc shaped slot to permit fine adjustment of the selected aperture angle. This configuration has three main disadvantages. First, at least one of the plurality of bolts required to attach the aperture need to be inserted and threaded before the aperture becomes self-supporting. Seemingly simple mechanical operations of this type are made much more difficult when they must be performed in exposed locations such as high atop a radio tower. Second, the assembly is relatively expensive to manufacture, because the plurality of arc shaped bolt slots require complex machining capabilities. Also, the overall number of required separate components is significant, increasing a drop hazard during installation and maintenance. Third, to maintain the strength of the component, the arc shaped bolt holes have a minimal angular

adjustment range. To change the angle 90 degrees from vertical to horizontal polarization, or vice versa, the entire assembly must be removed, rotated and again supported while the initial bolt(s) are re-inserted and tightened.

[0006] Alternatively, a slip ring separate from the aperture has been used, adding additional costs and introducing additional potential failure points to the overall system while maintaining the drawbacks described hereinabove.

[0007] Competition within the communications component and or systems industry has focused attention on structural integrity, materials and manufacturing operations costs. Also, ease of installation and service is a growing component and or system selection consideration.

[0008] Therefore, it is an object of the invention to provide an apparatus that overcomes deficiencies in the prior art.

#### **BRIEF DESCRIPTION OF DRAWINGS**

[0009] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with a general description of the invention given above, and the detailed description of the embodiments given below, serve to explain the principles of the invention.

[0010] Figure 1 is an exploded isometric angled top side view of

a first embodiment of the invention.

[0011] Figure 2 is an isometric angled top side view of Figure 1, with the transition assembly seated against the feed assembly spigot.

[0012] Figure 3 is an isometric angled top side view of Figure 1, with the transition assembly seated against the feed assembly spigot and rotated to align the transition assembly with a first polarization groove.

[0013] Figure 4 is an isometric angled top side view of Figure 1, with the transition assembly seated against the feed assembly spigot and rotated to align the transition assembly with a second polarization groove.

[0014] Figure 5 is a cross sectional schematic side view of the first embodiment of the invention, applied to an antenna base casting with a self supported feed assembly hub.

#### **DETAILED DESCRIPTION**

[0015] A first embodiment of the invention is described with reference to Figures 1–5. A transition assembly 1 with a waveguide 2 there through is adapted to mate with the feed point, also known as the spigot 3, of an antenna feed assembly 5. The transition assembly 1 is retained against the spigot 3 at a spigot end 4 by a pair of clamping screw(s) 7 that engage a clamping groove 9 formed in an

outer surface 10 of the transition assembly 1. Cutout(s) 11 formed in the outer surface 10 of the transition assembly 1 extending from the spigot end 4 of the assembly to the clamping groove 9 allow the clamping screw(s) 7 to reach the clamping groove 9 without interference from the transition assembly 1 during an initial seating of the transition assembly 1 against the spigot 3. Then, rotation of the transition assembly 1 engages an outer edge of each clamping screw head 13 into the clamping groove 9, retaining the transition assembly 1 against the spigot 3.

[0016] An aperture 15 may be formed in the transition assembly 1 to configure the polarization of the antenna feed assembly 5. Alignment indicia 17, for example grooves, formed on both the transition assembly 1 and a mating surface of the, for example, antenna base 19 corresponding to a desired angular orientation of the transition assembly 1 with respect to the base 19 provide a quick reference for aligning the aperture 15 via rotation of the transition assembly 1. The aperture 15 may be machined directly into the transition assembly 1 or configured as a separate component which inserts into and is retained by the transition assembly 1, allowing the user to select from a range of different apertures 15, depending upon the

specific application at hand.

[0017] The clamping screw(s) 7 may be provided with a guide surface 21 formed in an area of the base 19 surrounding a portion of each clamping screw head 13. The guide surface(s) 21 are adapted to a level from the base 19 which corresponds to the clamping groove 9 whereby when the top of each of the clamping screw(s) 7 is flush with the top of the respective guide surface(s) 21 the clamping screw(s) 7 are aligned to engage the clamping groove 9 upon initial seating of the transition assembly 1 onto the spigot 3. To ensure that the clamping screw(s) 7 securely retain the transition assembly 1 over time, an anti-vibration coating 25 may be added to the clamping screw 7 threads and or contact surfaces of the clamping screw head(s) 13. Alternatively and or additionally, the anti-vibration coating 25 may be added to the clamping groove 9.

[0018] Sealing groove(s) 27 may be added to the spigot 3 and or transition assembly 1 to provide a seat for o-rings 29 or other gaskets used to seal the interconnection between the transition assembly 1 and the spigot 3 and or the transition assembly 1 and further waveguide components or a transmitter / receiver (not shown) connected to the

transition assembly 1 via, for example, screws mating with screw holes 31.

[0019] In use, the clamping screw(s) 7 are screwed into the base 23 to a level where the clamping screw head(s) 13 are flush with the guide surface(s) 21. The transition assembly 1 cutout(s) 11 are aligned with the clamping screw(s) 7 and the transition assembly 1 seated onto the spigot 3. The transition assembly 1 may then be rotated to engage the clamping screw head(s) 13 into the clamping groove 9. The transition assembly 1 is rotated until the alignment indicia 17 of a desired polarization are aligned. Precision adjustment of the polarization alignment may then be made with the initial alignment as the starting point. When aligned as desired, the clamping screw(s) 7 are tightened to secure the transition assembly 1 to the spigot 3.

[0020] When a change of polarization, for example from vertical to horizontal is desired, only the clamping screw(s) 7 need be partially loosened and the transition assembly 1 rotated and aligned as desired proximate the opposite alignment indicia 17. The waveguide and or other components attached to the transition assembly 1 need not be removed, because unless the transition assembly is fully



rotated to an alignment where the cutout(s) 11 are aligned with the clamping screw(s) 7, the transition assembly 1 is retained upon the spigot 3 by the clamping screw head(s) 13 engagement with the clamping groove 9.

[0021] If automated polarization control and or fine tuning is desired, the transition assembly 1 may be configured to be rotatable by having the clamping screws tightened to secure the clamp screw heads in the clamp groove but not to prevent rotation of the transition assembly 1 which may then be rotatably driven by a drive (not shown) anchored, for example by a boss 33 formed in the base 19.

[0022] Alternatively, rather than using the clamping screw head(s) 13, the clamping screw(s) 7 may use tabs, washers, keyed retaining rings or the like as means for engaging the clamping groove 9.

[0023] One skilled in the art will appreciate that the present invention may be cost effectively fabricated without requiring advanced machining operations. Manufacturing and installation efficiencies are also increased when one appreciates that minimizing the number of necessary interconnecting screws and or bolts reduces the total number of components.

[0024] The present invention brings to the art a cost efficient



quick turn–lock transition assembly 1 that may be aligned for either vertical or horizontal polarization without removing it from, for example, the feed assembly 5 of an antenna. Further, the present invention provides heretofore unavailable ease of installation and or service characteristics, including the ability to align the transition assembly 1 for either vertical or horizontal polarization without removing it from, for example, the feed assembly 5 of an antenna.

Table of Parts

1	transition assembly
2	waveguide
3	spigot
4	spigot end
5	antenna feed assembly
7	clamping screw
9	clamping groove
10	outer surface
11	cutout
13	clamping screw head
15	aperture
17	alignment indicia
19	base
21	guide surface

25	anti-vibration coating
27	sealing groove
29	o-ring
31	screw hole
33	boss

[0025] Where in the foregoing description reference has been made to ratios, integers, components or modules having known equivalents then such equivalents are herein incorporated as if individually set forth.

[0026] While the present invention has been illustrated by the description of the embodiments thereof, and while the embodiments have been described in considerable detail, it is not the intention of the applicant to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, representative apparatus, methods, and illustrative examples shown and described. Accordingly, departures may be made from such details without departure from the spirit or scope of applicant's general inventive concept. Further, it is to be appreciated that improvements and/or modifications may be made thereto without departing

from the scope or spirit of the present invention as defined by the following claims.